

TASKalfa MZ3200i: A revolutionary versatile printer

The Kyocera TASKalfa MZ3200i is a complete A3 MFP that blends outstanding security with unbeatable quality to match the needs of the modern workplace both today and tomorrow.



TASKalfa MZ3200i

BASIC SPECIFICATIONS

Configuration: BW MFP - Print/Scan/Copy/Optional Fax Speed (print only):

Letter: 32 ppm, Legal: 17 ppm, Ledger: 17 ppm Warm Up Time: 18 seconds or less (power on)

First Page Out: Copy: 4.3 seconds / Print: 4.9 seconds Display: 10.1" Color Touch Screen Control Panel

Memory/Hard Disk Drive: Std. 4GB RAM/32GB SSD/ 320GB HDD, 1TB HDD (option)

Duplex: standard stackless duplex supports $5.5" \times 8.5"$ to 11" x 17", 16 lb. Bond - 90 lb. Index (60 - 163gsm)

Standard Output Tray: 5.5" x 8.5" - 11" x 17"/250-sheets **Electrical Requirements:**

120V/60Hz/9.9A; 220-240V, 50/60Hz, 6.3A Typical Electricity Consumption (TEC): 120V: .37 kWh/week; 220V: .40 kWh/week **Dimensions:** 23.3" W x 27.4" D x 26.8" H

Weight: 178.5 lbs

Maximum Monthly Duty Cycle: 150,000 pages per month

PAPER SUPPLY

Paper Capacity: Standard 1,100-sheets; Maximum 4.100-sheets Standard Paper Sources: Dual 500-sheet travs. 100-sheet MPT. Auto Selection/Switching Standard Paper Size: Tray 1 - 5.5" x 8.5" - 11" x 17" Tray 2 - 5.5" x 8.5" - 11" x 17"

OPTIONAL PAPER SOURCES

MPT: 5.5" x 8.5" - 11" x 17"

PF-791 Dual 500-sheet tray option - 5.5" x 8.5" - 11" x 17" **PF-810** Dual 1,500-sheet tray option - 8.5" x 11"

PAPER WEIGHT

Trays: 16 lb. Bond – 90 lb. Index (60 – 163gsm) MPT: 12 lb. Bond - 140 lb. Index (45 - 256gsm) Input Materials: Standard/Optional Trays: Plain, Bond, Recycled, Transparency (OHP), Cardstock, Envelopes

SECURITY SPECIFICATIONS

Local Authentication, Network Authentication Encryption Communication (IPsec, HTTPS, TLS 1.3, LDAPS, SMTP/POP/FTPS over TLS, SNMPv3), TPM chipset (Trusted Platform Module), S/MIME, SCEP (auto certificate issuance/renewal), OCSP/CRL (certificate validation), Secure Boot (firmware authenticity verification), Run Time Integrity Check, HDD and Memory Overwrite (7x) Mode and HDD Data Encryption (256 bit),
Common Criteria (ISO/IEC-15408/EAL2), IEEE 2600.2, FIPS 140-2 for storage, HCD-PP and FIPS 140-2 for communication require Data Security Kit 10 option which provides enhanced IPsec encrypted communication

PRINT SPECIFICATION

Standard Controller: ARM Cortex-A53/1.6GHz PDLs/Emulations: PRESCRIBE, PCL6, KPDL3 (PS3), XPS, OPEN XPS, PDF; Optional (UG 34): IBM ProPrinter, Line Printer, LQ-850 Print Resolution: Up to 1200 x 1200 dpi Fonts: KPDL3, PCL6, Bitmap OS Compatibility: Windows: 10/11/Server 2012/Server 2012 R2/Server 2016/Server 2019; Mac OS X v10.0 or later; Chrome OS Mobile Printing: Apple AirPrint®, Mopria Print Service®, KYOCERA Mobile Print, KYOCERA MyPanel remote access Interfaces: Standard: 1000 Base-T/100-Base-Tx/10BASE-T (IPv6, IPv4, IPsec), 802.3az ready, High-Speed USB 3.0, 4 USB 2.0 Host Interfaces, 2 eKUIO Expansion Slots, IEEE 802.11b/g/n Wireless LAN (supports up to 98.5 feet) Optional: IEEE 802.11a/b/g/n/ac (IB-37 for 2.4/5GHz), 10/100/1000BaseTX (IB-50 for Dual NIC); IEEE 802.11b/g/n (IB-51 for Wireless LAN Interface (supports up to 328.1 feet)
Network Print and Supported Protocols: HTTPS, FTPS, SNMP v1/v2c/v3, Raw Port (Port 9100) TCP/IP, IPv4, IPv6, DHCP LPR, DNS, WSD Scan/Print Drivers: KX Driver, PCL Uni-Driver, KPDL Uni-Driver, Microsoft Universal Print Driver, Network Fax Driver, TWAIN Driver, WIA Driver, Status Monitor, Common Profile, Output to PDF, Security Watermark KYOCERA Print Center, MAC Driver, Chrome Print Driver, Linux Driver, KX PRESCRIBE Macro Generator, Windows Inbox Driver, Linux SANE Driver

Utilities: KYOCERA Net Viewer, KYOCERA Device Manager, Quick Setup, ID Register, Software Management Service, Upgrade Studio, Web Package Maker, Removal Tool, Wi-Fi Setup Tool, PDF Direct Print, Command Center RX; Kyocera Net Manager (option)

Scan Type: Color and Black & White Scanner Scan Resolution: 600/400/300/200 dpi, 200 x 100 dpi, 200 x 400 dpi

File Formats: TIFF, JPEG, XPS, OpenXPS, PDF/A-2.0 (MMR/JPG Compression/High Compression PDF); Option: Scan Extension Kit Text Searchable PDF;

MS Office File Types
Connectivity: 10 BASE-T/100 BASE-TX/1000 BASE-T (IPv4, IPv6, IPSec) TCP/IP, Hi-Speed USB supported protocols Scanning Functions: Scan-to-Folder (SMBv3), Scan-to-Email, Scan-to-FTPS over TLS, Scan-to-USB, PDF Digital Signatures, WSD Scan, Linux SANE Scan, TWAIN Scan, Specified Color Removal, Border Erase, Preview
Original Size: Up to 11" x 17" (Glass)

Drivers: TWAIN/WIA/Linux SANE Driver/WSD Scan

Acceptable Originals: 5.5" x 8.5" - 11" x 17"

DP-7140: Reverse Auto Document Processor/50-sheets Speed: Simplex: 50 ipm; Duplex: 16 ipm (BW/Color) Weight: Simplex: 13 lb. Bond — 90 lb. Index (35 — 160gsm) Duplex: 16 lb. - 32 lb. Bond (50 - 120gsm)

DP-7150: Reverse Auto Document Processor/140-sheets Speed: Simplex: 80 ipm; Duplex: 48 ipm (BW/Color) Weight: Simplex: 13 lb. Bond — 90 lb. Index (35 — 160gsm) Duplex: 16 lb. - 32 lb. Bond (50 - 120gsm)

DP-7160 (with multi-feed detection):

Dual Scan Document Processor/320-sheets Speed: Simplex: 100 ipm; Duplex: 200 ipm (BW/Color) Weights: Simplex: 13 lb. Bond — 120 lb. Index (35 — 220gsm) Duplex: 16 lb. - 120 lb. Index (50 - 220gsm)

DP-7170 (with multi-feed and staple detection):

Dual Scan Document Processor/320-sheets Speed: Simplex: 100 ipm; Duplex: 200 ipm (BW/Color) Weights: Simplex: 13 lb. Bond — 120 lb. Index (35 — 220gsm) Duplex: 16 lb. - 120 lb. Index (50 - 220gsm)

COPY SPECIFICATIONS

Copy Resolution: 600 x 600 dpi Image Mode: Text, Photo, Text/Photo, Graphic/Map Continuous Copy: 1 — 9,999

Additional Features: Auto Magnification, Auto Paper Select, Combine Copy, Mirror Image, Rotate Copy, Border Erase, Margin, Page Number, Form Overlay, Blank Page Skip, Specified Color Removal, Proof Copy, Preview, ID Card Copy Job Management: 1,000 User Codes, Job Build, Shortcut Keys,

Magnification/Zoom: Full Size, 4 Reduction, 4 Enlargement Preset Ratios, 25 - 400% in 1% Step Increments Document Box: Custom/Job

OPTIONAL FAX SPECIFICATIONS

Fax Type: Fax System 12 (option) Type/Data Compression: G3 Fax/MMR, MR, MH, JBIG Transmission Speed/Modem Speed: Less than 3 seconds/33.6 Kbps Fax Memory: Standard 170 MB **Driver:** Network Fax Driver Fax Functions: Network Fax, Duplex Transmission and Reception, Encrypted Transmission and Reception, Polling Transmission and Reception, Broadcast, Fax Server Integration, Fax Dedicated Paper Feed Tray, Fax Forwarding to email or file

OUTPUT & FINISHING OPTIONS²

OPTIONAL 1,000 SHEET FINISHER DF-71203

Stack/Staple Capacity: Main Tray: 1,000-sheets/50-sheets, (up to 24 lb. Bond [90gsm])

Paper Size: 5.5" x 8.5" – 11" x 17"
Paper Weight: 14 lb. Bond – 140 lb. Index (52 – 256gsm) Edge Staple Position: Top Left, Bottom Left, Center Bind Optional Punch PH-74: 2/3 Hole Punch Unit, supports 8.5" x 11" – 11" x 17"; 14 lb. Bond – 140 lb. Index Dimensions: 21.6" W x 24.4" D x 41.3" H

OPTIONAL 3.000 SHEET FINISHER DF-7913

Stack/Staple Capacity: Main Tray (A): 3,000-sheets; **Sub Tray (B):** 200-sheets; Sub Tray (C):50-sheets/65-sheets **Paper Size:** 5.5" x 8.5" — 11" x 17"

Paper Weight: 16 lb. Bond — 140 lb. Index (60 — 256gsm) Edge Staple Position: Top Left, Bottom Left, Center Bind Dimensions: 29" W x 26" D x 42" H

Optional Punch PH-7A: 2/3 Hole Punch Unit

supports 8.5" x 11" - 11" x 17"; 14 lb. Bond - 140 lb. Index Optional Multi-Bin Mailbox MT-730(B): (DF-791) 7 Trays; supports: 16 lb. Bond — 90 lb. Index (60 — 163gsm);

Stack Capacity per bin: 100-sheets: 5.5" x 8.5", 8.5" x 11"; 50-sheets: 8.5" x 14", 11" x 17"

ADDITIONAL OPTIONS

AK-740 Bridge Unit Attachment Kit, HD-16 Large Capacity HDD (1TB), Internet Fax Kit (A), Card Authentication Kit (B), Data Security Kit 10, 2.4GHZ/5GHz Multi-band Wi-Fi option (IB-37), Dual NIC (IB-50), Extended Range Wireless LAN NIC (IB-51), Thin Print option (UG-33), Printer Emulation option (UG-34), DT-730(B) Document Tray, Scan Extension Kit (A) for Text Searchable PDF; Keyboard Holder 10, Numeric Keypad (NK-7130), Cabinet Stand

Only 1 Document Processor can be installed Only 1 Output Option can be installed ³ Requires Bridge Unit Attachment Kit (AK-740)

SOLUTIONS AND SERVICES

Remote Management: Kyocera Fleet Services ready! A highly secure cloud-based monitoring solution that offers real-time visibility into your fleet. Optimize device uptime and be notified when to replenish supplies. Streamline billing with seamless 3rd party application integration, allowing you to focus solely on

Printing Software: Cost Control & Security, Cloud & Mobile,

Content Services: Scanning Applications and Connectors, Intelligent Process Automation, Enterprise Content Management

IT Solutions: Technology Solutions (incl. Data Centers and Cloud), Network Infrastructure, Cybersecurity Solutions Collaboration Solutions

Consulting Services: IT Health Check, CIO as a Service, Healthcare Compliance, Backup and Recovery Planning

Professional Services: Design and Architecture, Project Implementation, Project Management

Managed Services: Help Desk Services. Retainer Services and Onsite Support


for the DF-791 Finisher

Resides in the Finisher

Staples up to 65-sheets

Document Processing Options





IB-51 Wireless LAN NIC **UG-34 Optional Printer** PLATEN TYPE E Scan Extension Kit (A) Keyboard Holder 10 **UG-33 Thin Print** (extended range) Emulation

5.5" x 8.5" to 11" x 17"

8.5" x 11"

IB-50 Gigabit Ethernet

Board for Dual NIC

DT-730 (B) Original Hard

Copy Holder



Specifications and design are subject to change without notice. TASKalfa, PRESCRIBE, Kyocera Net Manager, Kyocera Net Viewer, Kyocera Device Manager, PDF Direct Print, Command Center RX, and KX Driver are trademarks of The Kyocera Companies. Mac OS and AirPrint are trademarks of Apple, Inc. Mopria is a trademark of Mopria Alliance, Inc. Windows is a trademark of Microsoft, Inc. All other trademarks are the property of their respective owners.







KYOCERA Document Solutions America 225 Sand Road, PO Box 40008 Fairfield, New Jersey 07004-0008, USA Tel: 973-808-8444



Kyocera Document Solutions Partner

kyoceradocumentsolutions.us